

Appl. No. 10/811,289  
Amdt. dated January 31, 2005  
Reply to Office Action of November 17, 2004

### Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of Claims

1. (currently amended) A switch device operable in two steps, the switch device comprising:

a first switch;

a second switch;

a button, inclinable in a first direction for activating the first switch and a second direction[[,]] for activating the ~~first and/or~~ second switch, the button being inclinable to a first operation position and a second operation position when inclined in the first direction and being inclinable to a third operation position and a fourth operation position when inclined in the second direction; [[and]]

a pusher arranged between the button and the first and second switches, the pusher being movable when the button is pushed, the pusher comprising a first extension and a second extension; and

a switch body for supporting the button in an inclinable manner and for accommodating the pusher, the switch body including a first receiving portion for contacting the first extension of the pusher when the button is inclined in the first direction and a second receiving portion for contacting the second extension of the pusher when the button is inclined in the second direction,

wherein

inclination of the button in the first direction to the first operation position moves the pusher to solely activate the first switch;

further inclination of the button in the first direction to the second operation position moves the pusher about a position of contact between the first extension and the first receiving portion to activate the second switch in addition to the first switch;

inclination of the button in the second direction to the third operation position moves the pusher to solely activate the second switch; and

**BEST AVAILABLE COPY**

Appl. No. 10/811,289  
Amdt. dated January 31, 2005  
Reply to Office Action of November 17, 2004

further inclination of the button in the second direction to the fourth operation position moves the pusher about a position of contact between the second extension and the second receiving portion to activate the first switch in addition to the second switch.

2. (original) The switch device according to claim 1, wherein the pusher includes a first switch operator, facing towards the first switch, for activating the first switch, and a second switch operator, facing towards the second switch, for activating the second switch.

3. (currently amended) The switch device according to claim 2, wherein the pusher ~~further includes~~ a first extension and the ~~the~~ <sup>[[a]]</sup> second extension are respectively arranged opposite the first and second switch operators, and the switch device further comprising:  
~~— a switch body for supporting the button in an inclinable manner and for accommodating the pusher, the switch body including a first receiving portion for contacting the first extension of the pusher when the button is inclined in the first direction and a second receiving portion for contacting the second extension of the pusher when the button is inclined in the second direction;~~  
wherein the button includes a first pushing portion for pushing a first portion located at a first extension side of a top of the pusher and a second pushing portion for pushing a second portion located at a second extension side of the top of the pusher; and

~~— the pusher is moved about a position of contact between the first extension and the first receiving portion when the button is inclined from the first operation position to the second operation position to activate the second switch, and the pusher is moved about a position of contact between the second extension and the second receiving portion when the button is inclined from the third operation position to the fourth operation position to activate the first switch.~~

4. (currently amended) A switch device operable in two steps, the switch device comprising:

a first switch including a first fixed contact and a first movable contact associated with the first fixed contact;

Appl. No. 10/811,289  
Amtd. dated January 31, 2005  
Reply to Office Action of November 17, 2004

a second switch including a second fixed contact and a second movable contact associated with the second fixed contact;

a pusher movably arranged on the first and second movable contacts, the pusher including a first switch operator, arranged in association with the first movable contact, for activating the first switch and a second switch operator, arranged in association with the second movable contact, for activating the second switch; the pusher further including a first extension and a second extension respectively arranged opposite the first and second switch operators;

a switch body for supporting the button in an inclinable manner and for accommodating the pusher, the switch body including a first receiving portion for contacting the first extension of the pusher when the button is inclined in the first direction and a second receiving portion for contacting the second extension of the pusher when the button is inclined in the second direction;  
and

a button including a first pushing portion for pushing a first portion located at a top of the pusher in correspondence with the first switch and a second pushing portion for pushing a second portion located at the top of the pusher in correspondence with the second switch, the button being inclinable in a first direction to push the pusher with the first pushing portion and being inclinable in a second direction to push the pusher with the second pushing portion, the button being inclinable to a first operation position and a second operation position when inclined in the first direction and being inclinable to a third operation position and a fourth operation position when inclined in the second direction, wherein

inclination of the button in the first direction to the first operation position moves the pusher and solely activates the first switch with the first switch operator;

further inclination of the button in the first direction to the second operation position further moves the pusher and activates the second switch with the second switch operator in addition to the first switch;

inclination of the button in the second direction to the third operation position moves the pusher and solely activates the second switch with the second switch operator;  
and

Appl. No. 10/811,289  
Amdt. dated January 31, 2005  
Reply to Office Action of November 17, 2004

further inclination of the button in the second direction to the fourth operation position further moves the pusher and activates the first switch with the first switch operator in addition to the second switch; and  
wherein the pusher is moved about a position of contact between the first extension and the first receiving portion when the button is inclined from the first operation position to the second operation position to activate the second switch, and the pusher is moved about a position of contact between the second extension and the second receiving portion when the button is inclined from the third operation position to the fourth operation position to activate the first switch.

5. (canceled)

6. (Currently amended) The switch device according to claim [[5]] 4, wherein the first receiving portion includes a first receiving surface for receiving the first extension at a generally right angle, and the second receiving portion includes a second receiving surface for receiving the second extension at a generally right angle.

7. (original) The switch device according to claim 4, wherein the load required for activating the first switch is substantially equal to the load required for activating the second switch.

8. (original) The switch device according to claim 4, wherein the first switch includes a resiliently deformable first dome having a concave surface, and the second switch includes a resiliently deformable second dome having a convex surface, the first movable contact being arranged on the concave surface of the first dome, and the second movable contact being arranged on the concave surface of the second dome.

9. (original) The switch device according to claim 8, wherein the first dome and the second dome have substantially the same shape and size.

Appl. No. 10/811,289  
Amdt. dated January 31, 2005  
Reply to Office Action of November 17, 2004

10. (original) The switch device according to claim 4, wherein the pusher has a shape that is substantially symmetrical about its centerline, and the first and second pushing portions of the button push the pusher at positions equally spaced from the centerline of the pusher.

11. (original) A switch device operable in two steps, the switch device comprising:

a first switch;

a second switch;

a pusher movably arranged on the first and second switches, the pusher including a first switch operator, arranged in association with the first switch, for activating the first switch, a second switch operator, arranged in association with the second switch, for activating the second switch, and a first extension and a second extension respectively arranged opposite the first and second switch operators;

a switch body for accommodating the pusher, the switch body including a first receiving portion for contacting the first extension of the pusher and a second receiving portion for contacting the second extension of the pusher; and

a button supported by the switch body in an inclinable manner, the button including a first pushing portion for pushing a first portion located at a top of the pusher in correspondence with the first switch and a second pushing portion for pushing a second portion located at the top of the pusher in correspondence with the second switch, the button being inclinable in a first direction to push the pusher with the first pushing portion and being inclinable in a second direction to push the pusher with the second pushing portion, the button being inclinable to a first operation position and a second operation position when inclined in the first direction and being inclinable to a third operation position and a fourth operation position when inclined in the second direction, wherein

inclination of the button in the first direction to the first operation position moves the pusher and solely activates the first switch with the first switch operator,

further inclination of the button in the first direction to the second operation position further moves the pusher about a position of contact between the first extension and the first receiving portion to activate the second switch with the second switch operator in addition to the first switch;

Appl. No. 10/811,289  
Amdt. dated January 31, 2005  
Reply to Office Action of November 17, 2004

inclination of the button in the second direction to the third operation position moves the pusher and solely activates the second switch with the second switch operator; and

further inclination of the button in the second direction to the fourth operation position further moves the pusher about a position of contact between the second extension and the second receiving portion to activate the first switch with the first switch operator in addition to the second switch.

12. (currently amended) A vehicle window drive apparatus for opening and closing a vehicle window, the vehicle window drive apparatus comprising:  
a switch device operated to open and close the vehicle window, the switch device including;

a first switch including a first fixed contact and a first movable contact associated with the first fixed contact;

a second switch including a second fixed contact and a second movable contact associated with the second fixed contact;

a pusher movably arranged on the first and second movable contacts, the pusher including a first switch operator, arranged in association with the first movable contact, for activating the first switch and a second switch operator, arranged in association with the second movable contact, for activating the second switch; and a first extension and a second extension respectively arranged opposite the first and second switch operators;

a switch body for accommodating the pusher, the switch body including a first receiving portion for contacting the first extension of the pusher and a second receiving portion for contacting the second extension of the pusher; and

a button including a first pushing portion for pushing a first portion located at a top of the pusher in correspondence with the first switch and a second pushing portion for pushing a second portion located at the top of the pusher in correspondence with the second switch, the button being inclinable in a first direction to push the pusher with the first pushing portion and being inclinable in a second direction to push the pusher with the second pushing portion, the button being inclinable to a first operation position and a

Appl. No. 10/811,289  
Amdt. dated January 31, 2005  
Reply to Office Action of November 17, 2004

second operation position when inclined in the first direction and being inclinable to a third operation position and a fourth operation position when inclined in the second direction, wherein

inclination of the button in the first direction to the first operation position moves the pusher and solely activates the first switch with the first switch operator to keep the window moving in an opening direction as long as the first switch remains activated;

further inclination of the button in the first direction to the second operation position further moves the pusher about a position of contact between the first extension and the first receiving portion to activate ~~and activates~~ the second switch with the second switch operator in addition to the first switch to completely open the window;

inclination of the button in the second direction to the third operation position moves the pusher and solely activates the second switch with the second switch operator to keep the window moving in a closing direction as long as the second switch remains activated; and

further inclination of the button in the second direction to the fourth operation position further moves the pusher about a position of contact between the first extension and the second receiving portion to activate ~~and activates~~ the first switch with the first switch operator in addition to the second switch to completely close the window.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**